Drum Silencers Instructions

QUIET ON THE SET





Bass Drum Silencer Instructions

Bass Drum Silencer consists of the following parts:

- 1 Bass Drum Silencer (Foam Disc)
- 2 Rubber Bands
- 4 Stand Off's
- 4 "S" Hooks



- 1. Thread one rubber band through 2 Stand offs.
- 2. Attach an "S" hook at each end of the rubber band that can be used with Key Rods or T-Rods.
- 3. Hold the Bass Drum Silencer disc against your bass drum head.
- 4. Doing one side at a time, attach "S" hook to a key rod (see photo A) stretch each rubber band across your bass drum head, doing the top first. Make sure not to twist the rubber bands. If your bass drum has key rods, (see photo A) make sure that the rubber bands are secure on the key rods before you stretch them to the opposite key rod. The "S" hooks are provided to attach the rubber bands to bass drums that have key rods instead of T-rods. They can be used with either
- 5. Position the stand offs, with their flat side touching the foam disc, about a third of the way on the rubber band.

Cymbal Silencers Instructions

- 1. Remove the wing nut and top felt washer from your cymbal stand.
- 2. Place the Cymbal Silencer through the threaded stem so it lays on top of the cymbal.
- 3. Replace the top felt washer and the wing nut. The Cymbal Silencer will allow you to play directly on either the cymbal or the Cymbal Silencer. When riding or crashing on a cymbal, play directly on the Cymbal Silencer for the best sound reduction.

Hi Hat Silencer Instructions

- 1. Remove the top cymbal from your hi-hat stand.
- 2. Remove the hi-hat clutch from the top cvmbal.
- 3. Place the Hi-Hat Silencer on the top cymbal so the hole in the Silencer lines up with the hole in the top cymbal.
- 5. Replace the hi-hat clutch like you would when you normally set up your hi-hat stand. For sound reduction, play directly on the top of the Hi-Hat Silencer