

Installation:

1. Install Female (Flat Ring):

1. Remove drum head. Place the drum head face down with the rim edge up, on a smooth clean surface.
2. Select a location on the drum head, where the BASS DRUM O's is to be placed. Leave at least a 2" distance from the edge of the bass drum rim and the BASS DRUM O's. We recommend BASS DRUM O's placement, away from the center of the head, for as much front-head tone, as possible.
3. Clean the area where the BASS DRUM O's is to be placed with the alcohol swab in the packet. After cleaning, dry the surface area with a clean cloth.
4. Remove the protective paper from the female flat ring gasket. **DO NOT TOUCH THE ADHESIVE.**
5. Place the flat female piece, gasket side down, on the selected cleaned area, of the drum head. Press evenly and make sure there is contact, all the way around.

2. Cutting The Hole:

1. Place the drum head, face down, on a cutting mat or on a flat piece of scrap cardboard. Using an Xacto type razor blade, prepare to cut along the inside edge of the already attached flat female ring.
2. SLOWLY CUT, at a slight 30 degree angle, using the inside edge, of the female flat ring, as a guide. **MAKE SURE TO NOT CUT THE PLASTIC BASS DRUM O's.** Completely cut out the circle and make sure it is detached. Do not rip or force the hole. It may tear and destroy the drum head.

3. Install Male (Front Ring):

1. Clean the front area of the bass drum head, around the edge of the hole, with the alcohol swab. If the drum head is coated or painted, remove the paint, at least 3/8" from the edge of the hole (try scraping with a razors edge.)

2. Remove the protective paper from the male ring gasket of the BASS DRUM O's. **DO NOT TOUCH THE ADHESIVE.**
3. Moisten the contact edge, of the male ring, with the alcohol swab to help lubricate the connecting process.
4. Place the male ring, face down, on a clean table. Take the drum head, face down and fit one edge, of the female ring, onto the male ring. With one hand, hold the female ring edge firmly under the lip of the male ring. With the other hand, press the female ring until the entire ring is locked under the lip of the male ring.

**BASS
DRUM** 